

**Design Features**


- Flow meters for liquid flow applications.
- Jewel bearings allow for very low minimum flow rates.
- Easy to install and operate.
- Mounted horizontally or vertically.
- Only one moving part.
- Flow indication via transparent acrylic cover.
- Versatile square wave flow output signal.
- Female NPT ports.
- Multi-Parameter: Flow and temperature \*outputs.
- Four wires platinum RTD option.
- Polypropylene and chemically resistant.
- PVDF models.

\* PWM provides only raw pulse output signals. In order to get actual flow and temperature readings, user has to implement additional signal processing.

**Principles of Operation**

Fluid flowing through the unit causes the paddle wheel to spin. As the magnets embedded in the paddle spin past the sensor, electrical pulses are produced in which frequency is proportional to the flow rate. The number of pulses per desired time interval and the K-factor (number of pulses/gallon) make it possible to calculate the flow rate and volume passing through the unit.

**Configure and Order Online: [PWM Paddle-Wheel Flow Meter](#)**



**FOR LIQUIDS ONLY**

**TABLE 43 - FLOW RATE FOR PWM**

Meter Sizes	Flow Rate H <sub>2</sub> O		Inlet/Outlet Ports Female NPT	Max Pressure Drop	
	[L/min]	[gal/min]		Bar	PSI
PWM04	0.15-18.9	0.04-5	3/8"	1	15
PWM06	0.3-37.6	0.08-10	1/2"	1.4	20
PWM08	0.6-64.4	0.15-17	3/4"	1.4	20
PWM10	1.3-132.5	0.35-35	1"	1.4	20

**TABLE 45 - PADDLE WHEEL MODEL NUMBERS**

Polypropylene	Polypropylene with RTD	PVDF	PVDF with RTD
PWM04P	PWM04PR	PWM04T	PWM04TR
PWM06P	PWM06PR	PWM06T	PWM06TR
PWM08P	PWM08PR	PWM08T	PWM08TR
PWM10P	PWM10PR	PWM10T	PWM10TR

**TABLE 44 - SPECIFICATIONS**

<b>ACCURACY</b>	±1% FS.
<b>MAX TEMPERATURE</b>	60 °C (140 °F).
<b>MAX PRESSURE</b>	10 barg (150 psig).
<b>POWER</b>	5 to 24 Vdc @ 2 mA.
<b>OUTPUT SIGNAL</b>	NPN open collector (load 30 mA max).
<b>DIMENSIONS</b>	56H x 108L x 53D [mm] (2.2 x 4.25 x 2.2") Without RTD and flow sensors.
<b>CABLE</b>	Flow signal 1.8 m (6') or optional 3.7m (12') [ft.] RTD 12 [in.] long cable.
<b>RTD</b>	Platinum 0.00385 TCR, meets EN 60751, Class B.

**TABLE 46 - MATERIALS FLUID CONTACT:**

	POLYPROPYLENE MODELS	PVDF UNITS MODELS
<b>BODY</b>	Polypropylene	PVDF
<b>LID</b>	Acrylic	PVDF
<b>PADDLE WHEEL</b>	PVDF	PVDF
<b>SHAFT</b>	Nickel Tungsten Carbide	Zirconia Ceramic
<b>BEARINGS</b>	Sapphire Jewels	Sapphire Jewels
<b>O-RINGS</b>	EPDM	PTFE
<b>PLATINUM RTD</b>	316 ss casing	316 ss casing